

2SK2848

外形図1.....FM20

絶対最大定格

(Ta = 25°C)

記号	定格	単位
V _{DSS}	600	V
V _{GSS}	±30	V
I _D	±2	A
I _D (pulse) ¹	±8	A
P _D	30(Tc = 25°C)	W
E _{AS} ²	10	mJ
I _{AS}	2	A
T _{ch}	150	°C
T _{stg}	-55 ~ +150	°C

1: P_w 100μs, duty cycle 1%

2: V_{DD} = 30V, L = 5mH, I_L = 2.0A, unclamped, R_G = 50Ω, P5図1参照

電気的特性

(Ta = 25°C)

記号	規格値			単位	条件
	min	typ	max		
V(BR) _{DSS}	600			V	I _D = 100μA, V _{GS} = 0V
I _{GSS}			±100	nA	V _{GS} = ±30V
I _{DSS}			100	μA	V _{DS} = 600V, V _{GS} = 0V
V _{TH}	2.0	3.0	4.0	V	V _{DS} = 10V, I _D = 250μA
Re(y _{fs})	1.2	1.7		S	V _{DS} = 20V, I _D = 1A
R _{DS(on)}		3.0	3.8		V _{GS} = 10V, I _D = 1A
C _{iss}		290		pF	V _{DS} = 10V, f = 1.0MHz, V _{GS} = 0V
C _{oss}		70		pF	
C _{rss}		30		pF	
t _{d(on)}		16		ns	I _D = 1A, V _{DD} = 250V, R _L = 250Ω, V _{GS} = 10V, P5図2参照
t _r		30		ns	
t _{d(off)}		45		ns	
t _f		145		ns	
V _{SD}		0.9	1.4	V	I _{SD} = 2.0A, V _{GS} = 0V



